

SUREBAND^{Clear}

Ideal for Acid / Caustic / E15 Oil and Diesel mist prevention

Manufactured from All-PTFE materials (no fibreglass) comprising clear ECTFE outer and multi-layered ETFE mesh inner. This material provides unparalleled chemical resistance. All our shields are tested on our hydrostatic pressure test facility, test certificates available on request.

The internal mesh is compressed against the flange and prevents direct and lateral spray. The liquid pressure inside is rapidly diffused, resulting in a safe drip-release.

SUREBAND^{Clear} is very quick to install using heavy duty Velcro tabs which have been leak tested at various orifice sizes at pressure up to 75 Bar. It can be re-used in the event of a leak, thus providing a long term solution.

Specification

| | |
|-----------------------|--------------------------|
| Band Material: | ECTFE |
| Mesh Material: | ETFE |
| Fastener: | Heavy Duty Velcro |
| Shear force: | 196 N |
| Max Temperature: | 200 Deg C |
| Flange Ratings: | ANSI / DIN / many others |
| Pipe Sizes: | 15mm to 1200mm |
| Leak Detection: | Visual Litmus Paper |
| Typical Applications: | Acid, Bases, Oil |



This product can also be made to fit valves and other non-standard pipe joints, contact us for further information

